## PHANTOM Prop Guard Assembly Instruction V1.02

## PHANTOM 桨保护器安装说明 v1.02

Please carry out the following procedures to attach the Prop Guard to the aircraft.

## 请按照下面步骤安装奖保护器。

- 1. Prepare the aircraft, Prop Guard (4 pcs), M3.0x12 Screws (8 pcs), a thread and an allen driver.

  准备 PHANTOM 飞行器、桨保护器(4 个)、M3.0x12 螺丝(8 颗)、保护线、内六角螺丝刀。
- 2. Use the screw driver to remover the screws on the four motors (M3.0x8) of PHANTOM marked in blue in Fig.1. 使用螺丝刀卸下原 PHANTOM 四个电机上的螺丝(M3.0x8)。(如图 1 蓝色标记)
- Fix the Screws of M3.0x12 with appropriate strength (Fig.1) to mount the four Prop Guards on the PHANTOM.
   Note that thread lock is not allowed.
  - 按照图 1 所示,适当用力拧紧螺丝(M3.0x12),装好四个 PHANTOM 桨保护器。不可以使用螺丝胶。
- 4. For better protection, please attach a thread through the Prop Guard, note that the thread should be under the Prop Guards (Fig.2). Finish.

为了起到更好的保护作用,可按照图 2 所示,将保护线连到桨保护器上,注意穿线时线都在桨保护器底部。安装完毕。



IMPORTANT: Here, M3.0x12 Screw is for Prop Guard assembly. Without Prop Guard, you should use M3.0x8 Screw; otherwise, wrong type of screw will damage the motor.

注意: 此处安装桨保护器,使用型号为 M3.0x12 的螺丝;如果没有安装桨保护器,只能使用型号为 M3.0x8 螺丝。否则,过长的螺丝会损坏电机。

Fig.1 Prop Guard Installation Diagram /图 1 桨保护器安装示意图



Fig.2 Installation is OK/图 2 正确安装示意图

## Specifications/参数

**Weight ( Single ) /重量 ( 单个 )**: 18.7g **Size(Single)/单个尺寸**: Angle/角度(155.0°)

Radius/半径(112.32mm)

Whole Size with Four Prop Guards /安装后最大

外形尺寸:575.5mm