
# **MATRICE 200**

User Manual V1.0

2017.06





### Q Searching for Keywords

Search for keywords such as "battery" and "install" to find a topic. If you are using Adobe Acrobat Reader to read this document, press Ctrl+F on Windows or Command+F on Mac to begin a search.

### Navigating to a Topic

View a complete list of topics in the table of contents. Click on a topic to navigate to that section.

## Printing this Document

This document supports high resolution printing.

### **Using this manual**

### Legends

### Before Flight

The following materials have been produced to help users make full use of the MATRICE™ 200.

- 1. In the Box
- 2. Safety Guidelines and Disclaimer
- 3. Quick Start Guide
- 4. Intelligent Flight Battery Safety Guidelines
- 5. User Manual

Watching all the tutorial videos and reading the Disclaimer before flight is recommended. Afterwards, prepare for your first flight by using the Quick Start Guide. Refer to this manual for more comprehensive information.

### Watch the video tutorials

Please watch the tutorial video below to learn how to use Matrice 200 correctly and safely: <a href="http://www.dji.com/matrice-200-series/info#video">http://www.dji.com/matrice-200-series/info#video</a>



### Download the DJI GO 4 app

Download and install the DJI  $GO^{TM}$  4 app before use. Scan the QR code or visit "https://m.dji.net/djigo4" to download the app.



For the best experience possible, use mobile devices running Android v4.4 or iOS v9.0 or above.

### Download the DJI Assistant 2

Download and install the ASSISTANT<sup>™</sup> 2 before use. http://www.dji.com/matrice-200-series/info#downloads

### **Contents**

Using this manual	2
Legends	2
Before Flight	2
Watch the video tutorials	2
Download the DJI GO 4 app	2
Download the DJI Assistant 2	2
Product Profile	5
Introduction	6
Feature Highlights	6
Assemble the Aircraft	6
Preparing Remote Controller	8
Aircraft Diagram	9
Remote Controller Diagram	10
Aircraft	12
Flight Controller	13
Flight Mode	13
Flight Status Indicator	14
Vision System and Infrared Sensing System	15
Return-to-Home (RTH)	20
Intelligent Flight Modes	24
Flight Recorder	29
Attaching and Detaching the Propellers	29
DJI Intelligent Flight Battery	29
Remote Controllers	36
Remote Controller Profile	37
Remote Controller Operations	37
Dual Remote Controller Mode	42
Remote Controller Status LED	44
Linking the Remote Controller	45
Gimbal and Camera	47
Camera	48
Gimbal	49

DJI GC	0.4	51
	Equipment	52
	Editor	56
	SkyPixel	56
	Me	56
Flight		57
	Flight Environment Requirements	58
	Flight Limits and No-Fly Zones	58
	Preflight Checklist	61
	Calibrating the Compass	61
	Auto Takeoff and Auto Landing	62
	Starting/Stopping the Motors	63
	Stop the Motor Mid-flight	63
	Flight Test	64
Appen	dix	65
	Specifications	66
	Aircraft Status Indicator Description	69
	Upgrading the Firmware	69
	After-Sales Information	70

## **Product Profile**

This chapter describes the features of the Matrice 200, shows how to assemble the aircraft, and contains diagrams of the aircraft and remote controller with component explanations.

### **Product Profile**

### Introduction

The Matrice 200 is a powerful aerial imaging system with class-leading agility and speed, redundant components for maximum reliability, and new smart features that make performing complex tasks easy. Gimbal cameras can be easily exchanged to suit your application's needs. Dual frequency remote controller transmission makes HD video downlink more stable and efficient. Upgraded With TapFly<sup>TM</sup> and ActiveTrack<sup>TM</sup> flight modes, the Matrice 200 can fly anywhere you tap on screen and track moving subjects effortlessly.

### Feature Highlights

The Matrice 200's mechanical design, along with quick-release landing gears and folding arms, makes it easy to transport, store, and prepare for flight. The drone's new airframe design gives it an IP43 Ingress Protection Rating, in accordance with the global IEC 60529 standard.

Flight Controller: The flight controller has been updated to provide a safer, more reliable flight experience. A new flight recorder stores critical data from each flight. A system of visual sensors enhance hovering precision when flying indoors or in environments where GPS is unavailable. Dual IMUs and barometers design provides redundancy.

HD Video Downlink: The low-latency long range (up to 4.3mi (7km)) HD downlink is powered by an enhanced version of DJI LIGHTBRIDGE™. Support of 2.4 GHz and 5.8 GHz ensures a more reliable connection in environments with more interference.

Camera and Gimbal: The camera unit is now independent from image processor so that you have the flexibility to choose the perfect gimbal and camera system (including ZENMUSE™ X5S、X4S、XT\*, and Z30) for each of your application. This means that regardless of which camera you choose, you have the same powerful processing backing it.


Intelligent Flight Battery: The Intelligent Flight Battery features upgraded battery cells and an advanced power management system. The drone provides up to 27 minutes of flight with standard batteries and 38 minutes with optional high-capacity batteries without payload.

\* The Zenmuse XT Gimbal Adapter is required when mounting the Zenmuse XT gimbal to the Matrice 200 series aircraft.

Both DJI GO 4 and DJI Pilot support the Zenmuse X5S, X4S, and Z30. DJI Pilot is required if using the Zenmuse XT.


### Assemble the Aircraft

### Installing the Landing Gears



### Unfolding the Aircraft

Unfold the frame arm, slide the arm lock to the end of the frame arm, then rotate it about  $90^\circ$  until the silver line lies within the range of the  $\iff$  icon.



### Mounting the Propellers



Propellers without silver rings go on motors without any marks.



Press the propeller down onto the mounting plate and rotate in the lock direction (a until secure.




Propellers with silver rings go on motors with the same color marks.



↑ Check that the propellers are secure before each flight.

### Mounting the Gimbal and Camera



detachment button to remove the cover.

and red dots and insert the gimbal.

Rotate the gimbal lock to the locked position.

 $\triangle$ 

Make sure to press down the gimbal detachment button when rotating the gimbal lock to remove the gimbal and camera. The gimbal lock should be fully rotated when removing the gimbal for the next installation.


### Mounting the Intelligent Flight Batteries

Insert the battery pair.

Press once to check the battery level.

Press once, again, and hold to turn on/off.






 $\triangle$ 

Only use battery slot B when using one battery to supply power.

### Removing the Intelligent Flight Battery

Make sure to press the battery removal button when removing the battery.



### **Preparing Remote Controller**


Tilt the Mobile Device Holder to the desired position then adjust the antennas as shown.

- 1. Press the button on the side of the Mobile Device Holder to release the clamp, attach your mobile device, then tighten the clamp to secure it.
- 2. Connect your mobile device to the remote controller with a USB cable.
- 3. Plug one end of the cable into your mobile device, and the other end into the USB port on the back of the remote controller.





### Aircraft Diagram





Folded

- 1. FPV Camera
- 2. Forward Vision System
- 3. DJI Gimbal Connector V2.0 (DGC2.0)
- 4. Gimbal and Camera Detachment Button
- 5. Frame Arms
- 6. Motors
- 7. Propellers
- 8. ESC LEDs
- 9. Landing Gear
- 10. Upward Infrared Sensor

- 11. Aircraft Status Indicator
- 12. Linking Button/Linking Indicator
- 13. USB Port
- 14. USB Mode Switch
- 15. Battery Removal Button
- 16. Intelligent Flight Batteries
- 17. Battery Level Indicators
- 18. Power Button
- 19. Downward Vision System
- 20. Micro SD Card Slot

### Remote Controller Diagram

### [1] Power Button

Used to turn the Remote Controller on and off.

### [2] Return-to-Home (RTH) Button

Press and hold to initiate Return to Home (RTH).

#### [3] Control Sticks

Control the orientation and movement of the aircraft.

#### [4] Status LED

Displays the Remote Controller's system status.

### [5] Battery Level LEDs

Display the battery level of the Remote Controller.

### [6] Power Port

Connect to the Charger to charge the battery of the remote controller.

#### [7] Mobile Device Holder

Securely mounts your mobile device to the remote controller.

### [8] Antennas

Relay aircraft control and video signals.

#### [9] Handle Bar

#### [10] Control Dial (Gimbal/FPV)

Use this dial to control gimbal tilt. In Free

Mode, pressing and holding the C1 Button and rotating the control dial adjusts gimbal pan. To adjust the tilt of the FPV camera, press and hold the C2 Button and rotate the control dial.

### [11] Camera Settings Dial


Turn the dial to adjust camera settings. (Only functions when the remote controller is connected to a mobile device running the DJI GO 4 app.)


#### [12] Record Button

Press to start recording video. Press again to stop recording.

### [13] Flight Mode Switch

Switch between P-mode, S-mode, and A-mode.





### [14] Shutter Button

Press the Shutter Button to take a photo. Photos can also be captured during video recording.

### [15] Pause Button

Press once to allow the aircraft to exit from TapFly, ActiveTrack, and Advanced mode.

#### [16] Micro USB Port

Use this port to upgrade the firmware.

### [17] CAN Bus

Reserved extended port.

### [18] HDMI A Port

HDMI A Port is for video output.

### [19] USB Port

Connection to mobile device for DJI GO 4 app.

### [20] C1 Button


Customizable through the DJI GO 4 app.

### [21] C2 Button

Customizable through the DJI GO 4 app.

## **Aircraft**

This section describes the features of the Flight Controller, Vision System, and the Intelligent Flight Battery.



### **Aircraft**

### Flight Controller

The Matrice 200 flight controller features several important upgrades. Safety modes include Failsafe and Return-to-Home. These features ensure the safe return of your aircraft if control signal is lost. The flight controller can also save critical flight data from each flight to the on-board storage device. The new flight controller also provides increased stability and a new air braking feature.

### Flight Mode

The following flight modes are available for Matrice 200:

### P-mode (Positioning):

P-mode works best when the GPS signal is strong. The aircraft utilizes the GPS and Forward and Downward Vision Systems to locate itself, automatically stabilize, and navigate between obstacles. Intelligent Flight Modes such as TapFly and ActiveTrack are enabled in this mode.

When the Forward Vision System is enabled and lighting conditions are sufficient, the maximum flight attitude angle is 25°. When forward obstacle sensing is disabled, the maximum flight attitude angle is 30°.

When the GPS signal is weak and lighting conditions are too dark for the Forward and Downward Vision Systems, the aircraft will only use its barometer for positioning to control

Note: P-mode requires larger stick movements to achieve higher speeds.

### S-mode (Sport):

The aircraft uses GPS for positioning. As Forward and Downward Vision Systems are disabled, the aircraft will not be able to sense and avoid obstacles when in Sport Mode. Ground Station and the Intelligent Flight functions are also not available in Sport Mode.

Note: Aircraft responses are optimized for agility and speed making it more responsive to stick movements.

### A-mode (Attitude):

When neither the GPS nor the Vision Systems are available, the aircraft will only use its barometer for positioning to control the altitude. Ground Station and the Intelligent Flight functions are also not available in A-mode




- ↑ The Forward Vision System is disabled in S-mode (Sport), which means the aircraft will not be able to automatically avoid obstacles in its flight path. Be vigilant and stay clear of nearby obstacles.
  - The aircraft's maximum speed and braking distance are significantly increased in S-mode (Sport). A minimum braking distance of 164 feet (50 meters) is required in windless conditions.
  - The aircraft's responsiveness is significantly increased in S-mode (Sport), which means a small stick movement on the remote controller will translate into a large travel distance of the aircraft. Be vigilant and maintain adequate maneuvering space during flight.
  - The aircraft's descent speed is significantly increased in S-mode (Sport). A minimum braking distance of 164 feet (50 meters) is required in windless conditions.



Use the Flight Mode switch on the remote controller to select aircraft flight modes.

### Flight Status Indicator

The aircraft features Front LEDs, a Rear LED, and Aircraft Status Indicators. The positions of these LEDs are shown in the figure below:



The Front LEDs show the orientation of the aircraft. Front LEDs glow solid red when the aircraft is turned on to indicate the front (or nose) of the aircraft. Front and rear LEDs can be turned off in the DJI GO 4 app. The Aircraft Status Indicators communicate the system status of the flight controller. Refer to the table below for more information about the Aircraft Status Indicators.


### Aircraft Status Indicator Description

Normal		
· · · · · · · · · · · · · · · · · · ·	Red, yellow, green, blue, and purple flashes	Turning On and Self Diagnostic Testing
<b>∀</b> ×4	Four yellow flashes	Warming Up
<u> </u>	Slow green flashing	P-mode with GPS*
© ×2 ······	Two green flashes	P-mode with Forward and Downward Vision Systems*
· <u>\(\tilde{\ti}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}</u>	Slow yellow flashing	No GPS and Forward and Downward Vision Systems
· (G):	Fast green flashing	Braking
Warning		
÷ (Ý)	Fast yellow flashing	Remote Controller Signal Lost
; <u>(</u> <u>R</u> ):	Slow red flashing	Low Battery Warning
: <u>®</u> :	Fast red flashing	Critical Low Battery Warning
: <u>``</u>	Red flashing	IMU Error
- <u>(R)</u> -	Solid Red	Critical Error
- <u>B</u> - <u>Y</u>	Fast alternating red and yellow flashing	Compass Calibration Required

<sup>\*</sup> Slow green flashes indicate P-mode, and fast green flashes indicate S-mode.


### Vision System and Infrared Sensing System

The main components of the Vision System are located on the front and bottom of the aircraft, including [1] [3] stereo vision sensors and [2] two ultrasonic sensors. The Vision System uses ultrasound and image data to help the aircraft maintain its current position, enabling precision hovering indoors or in environments where a GPS signal is not available. The Vision System constantly scans for obstacles, allowing the Matrice 200 to avoid them by going over, going around, or hovering. The Infrared Sensing System consists [4] of two infrared modules on top of the aircraft. These scan for obstacles on top side of the aircraft and is active in certain flight modes.




### **Detection Range**

The detection range of the Vision System is depicted below. Note that the aircraft cannot sense and avoid obstacles that are not within the detection range.



 $\triangle$  The aircraft cannot detect objects in low-light conditions. Please fly with caution.

Ultrasonic sensor detection range is depicted below.



Infrared Sensing System detection range is depicted below.




### Calibration

The Forward and Downward Vision System cameras are calibrated prior to delivery. However, these cameras are vulnerable to impact and will require occasional calibration via DJI Assistant 2.

#### Calibration with the included Visual Calibration Plate.

- 1. Power on the Intelligent Flight Battery and toggle the USB Mode Switch left.
- 2. Connect the Matrice 200 and the PC with a male to male USB cable.
- 3. Launch DJI Assistant 2 and log in with a DJI account.
- 4. Click M200SERIES and the calibration button.



- 5. Place the side of visual calibration plate with the dots facing the Forward Vision System, and follow the instructions in the DJI Assistant 2 to complete calibration.
- 6. Place the aircraft straight, and ensure the dotted side of the visual calibration plate faces the Downward Vision System. Follow the instructions in DJI Assistant 2 to complete calibration.

### Calibrating with a Screen

Follow the steps below to calibrate the camera.



⚠ DO NOT power off or unplug the USB cable after calibration. Wait for data calculation.

### Using the Vision System

The Vision System is activated automatically when the Matrice 200 is turned on. No further action is required. The Vision System enables precision hovering indoors or in environments where GPS signal isn't available.




Follow the steps below to use the Vision System:

- Ensure the aircraft is in P-mode and place the aircraft on a flat surface. Note that the Vision System cannot work properly on surfaces without clear pattern variations.
- 2. Turn on the aircraft. The aircraft will hover in place after takeoff. The aircraft status indicators will flash green twice, which indicates the Vision System is working. Gently push the left stick up to lift off and the aircraft will hover in place.



#### Assisted Braking from Obstacle Sensing

Powered by the Forward Vision System, the aircraft is able to actively brake when obstacles are detected in front. Obstacle Sensing works best when lighting is adequate and the obstacle is clearly textured. The aircraft must fly at no more than 31 mph (50 kph) to allow for sufficient braking distance.



### Using Infrared Sensing System

The Infrared Sensing System can only be used to avoid large, diffuse, and reflective obstacles (reflectivity >10%). Please be mindful of blind spots (Grey) of the Infrared Sensing System.



 $\triangle$ 

• The performance of your Vision System and Infrared Sensing System is affected by the surface being flown over. Ultrasonic sensors may not be able to accurately measure distances when operating above sound-absorbing materials and the cameras may not function correctly in suboptimal environments. The aircraft will switch from P-mode to A-mode automatically if neither GPS nor Vision System and Infrared Sensing System are available. Operate the aircraft with great caution in the following situations.

The Vision System will be disabled when:

- a) Flying over monochrome surfaces (e.g. pure black, pure white, pure red, pure green).
- b) Flying over highly reflective surfaces.
- c) Flying over water or transparent surfaces.
- d) Flying over moving surfaces or objects.
- e) Flying in an areas where the lighting changes frequently or drastically.
- f) Flying over extremely dark (lux < 10) or bright (lux > 100,000) surfaces.
- g) Flying over surfaces without clear patterns or texture.
- h) Flying over surfaces with identical repeating patterns or textures (e.g. tiling).
- Flying at high speeds of over 31 mph (50 kph) at 2 meters or over 11 mph (18 kph) at 1 meter

The Ultrasonic sensors will be disabled when:

- a) Flying over surfaces that can absorb sound waves (e.g. thick carpet).
- b) Flying over inclined surfaces that will deflect sound waves away from the aircraft. The Infrared be disabled when:
- a) Flying over obstacles with too small effective infrared reflective surface.
- b) DO NOT cover the protective glass of the infrared module. Keep it clean and undamaged.



- Keep sensors clean at all times. Dirt or other debris may adversely affect their effectiveness.
- Vision System is only effective when the aircraft is at altitudes of 0.3 to 10 meters.
- The Vision System may not function properly when the aircraft is flying over water.
- The Vision System may not be able to recognize pattern on the ground in low light conditions (less than 100 lux).
- Do not use other ultrasonic devices with frequency of 40 KHz when Vision System is in operation.
- Keep away from animals while operating the aircraft, as the ultrasonic sensors emit high-frequency sounds which may disturb them.

### Return-to-Home (RTH)

The Return-to-Home (RTH) function brings the aircraft back to the last recorded Home Point. There are three types of RTH: Smart RTH, Low Battery RTH, and Failsafe RTH. This section describes these three RTH types in detail.

<b>I</b>	GPS	Description	
Home Point	<b>%</b> adl	If a strong GPS signal was acquired before takeoff, the Home Point is the location from which the aircraft launched. The GPS signal strength is indicated by the GPS icon , Less than 4 bars is considered a weak GPS signal. The aircraft status indicator will blink rapidly when the home point is recorded.	



The aircraft can sense and avoid obstacles when the Forward Vision System is enabled and lighting conditions are sufficient. The aircraft will automatically ascend to avoid obstacles and descend slowly as it returns to the home point. To ensure the aircraft returns home while facing forward, it cannot rotate or fly left and right during RTH while the Forward Vision System is enabled.

#### Smart RTH


Use the RTH button on the remote controller or tap the RTH button in the DJI GO 4 app and follow the on-screen instructions when GPS is available to initiate Smart RTH. The aircraft will then automatically return to the last recorded Home Point. Use the remote controller to control the aircraft's speed or altitude to avoid a collision during the Smart RTH process. As the aircraft returns, it will use the primary camera to identify obstacles as far as 300m in front, allowing it to plan a safe route home. Press and hold the Smart RTH button once to start the process, and press the Smart RTH button again to terminate the procedure and regain full control of the aircraft.

#### Low Battery RTH (Can be turned off in DJI GO 4 app)

The low battery level failsafe is triggered when the DJI Intelligent Flight Battery is depleted to a point that may affect the safe return of the aircraft. Users are advised to return home or land the aircraft immediately when prompted. The DJI GO 4 app will display a notice when a low battery warning is triggered. The aircraft will automatically return to the Home Point if no action is taken after a tensecond countdown. The user can cancel the RTH procedure by pressing the RTH button on the remote controller. The thresholds for these warnings are automatically determined based on the aircraft's current altitude and distance from the Home Point.

The aircraft will land automatically if the current battery level can only support the aircraft long enough to descend from its current altitude. The user can still use the remote controller to alter the aircraft's orientation during the landing process.

The Battery Level Indicator is displayed in the DJI GO 4 app, and is described below:



Battery level Indicator

Battery Level Warning	Remark	Aircraft Status Indicator	DJI GO 4 App	Flight Instructions
Low battery level warning	Battery power is low. Land the aircraft.	Aircraft status indicator blinks RED slowly.	Tap "Go-home" to have the aircraft return to the Home point and land automatically, or "Cancel" to resume normal flight. If no action is taken, the aircraft will automatically go home and land after 10 seconds. Remote controller will sound an alarm.	Fly the aircraft back and land it as soon as possible, then stop the motors and replace the battery.
Critical Low battery level warning	The aircraft must land immediately.	Aircraft status indicator blinks RED quickly.	The DJI GO 4 app display will flash red and the aircraft will start to descend. The remote controller will sound an alarm.	Allow the aircraft to descend and land automatically.
Estimated remaining flight time	Estimated remaining time is based on current battery level.	N/A	N/A	N/A



- When the Critical Low battery level warning is triggered and the aircraft begins to land automatically, push the left stick upward to make the aircraft hover at its current altitude, giving you an opportunity to navigate to a more appropriate landing location.
- The colored zones and markers on the battery level indicator bar reflect the estimated remaining flight time. They are automatically adjusted according to the aircraft's current location and status

### Failsafe RTH

If the Home Point was successfully recorded and the compass is functioning normally, Failsafe RTH will be automatically activated if the remote controller signal is lost for more than three seconds. The aircraft will plan its return route and retrace its original flight route home. The user may cancel Failsafe RTH to regain control when connection is reestablished.

#### **RTH Procedure**


- 1. Home Point is recorded automatically.
- 2. RTH procedure is triggered i.e., Smart RTH, Low-Battery RTH, and Failsafe RTH.
- 3. Home Point is confirmed and the aircraft adjusts its orientation.
- 4. a. The aircraft will ascend to the pre-set RTH attitude and then fly to the Home Point when the aircraft is further than 20 m from the Home Point
  - b. When the aircraft is between 3 m and 20 m from the Home Point, it will return to the Home Point at the current altitude with the RTH at Current Altitude option enabled (the default setting in DJI GO 4) if flying at or above 2.5 m. It will ascend to 2.5 m then return to home if flying lower than 2.5 m.


Note: If RTH at Current Altitude is disabled in DJI GO 4, the aircraft will land automatically when the aircraft is between 3 m and 20 m from the Home Point.

- c. The aircraft will land automatically if RTH is triggered and the aircraft is less than 3 m from the home point.
- 5. The aircraft will hover 0.7 m above ground and wait for confirmation from the user. The aircraft will land and stop its motors after user confirmation.

### Use the Failsafe RTH for example:











- $\wedge$
- User cannot control the aircraft while the aircraft is ascending to 65 feet (20 meters) from the current altitude. However, users can press the RTH button once to exit ascending and regain control.
- The aircraft will automatically descend and land if RTH is triggered when the aircraft flies within a 65 feet (20 meters) radius of the Home Point. The aircraft will stop ascending and will return to the Home Point if the aircraft reaches 65 feet (20 meters) in altitude or beyond during Failsafe.
- The aircraft cannot avoid obstacles during Failsafe RTH if the Forward Vision System is disabled. It is important to set a suitable RTH Altitude before each flight. Launch DJI GO 4, enter camera and tap & to set Failsafe Altitude.

#### Failsafe Safety Notices



The aircraft cannot avoid obstacles during Failsafe RTH when the Forward Vision System is disabled. Therefore, it is important to set a suitable Failsafe altitude before each flight. Launch the DJI GO 4 app, enter Camera and tap  $\Re$  to set the Failsafe Altitude.



If the aircraft is flying under 65 feet (20 meters) and Failsafe (including Smart RTH, Lower Battery RTH) is triggered, the aircraft will first automatically ascend to 65 feet (20 meters) from the current altitude. You can only cancel the ascending by exiting the Failsafe.



The aircraft automatically descends and lands if RTH is triggered when the aircraft flies within a 65 foot (20 meter) radius of the Home Point. The aircraft will stop ascending and immediately return to the Home Point if you move the left stick when the aircraft is flying at an altitude of 65 feet (20 meters) or higher and Failsafe is triggered.



The aircraft cannot return to the Home Point when GPS signal is weak ([ & || || ] displaying less than four bars) or is unavailable.





If you move the left stick when the aircraft is flying above 65 feet (20 meters) but below the pre-set Failsafe RTH altitude, the aircraft will stop ascending and immediately return to the Home Point.

### Obstacle Avoidance During RTH\*

The aircraft can sense and actively attempt to avoid obstacles during RTH, provided that lighting conditions are adequate for the Forward Vision System. Upon detecting an obstacle, the aircraft will act as follows:

- 1. The aircraft will use the primary camera to identify obstacles as far away as 984 feet (300 meters) in front, allowing it to plan a safe route home.
- 2. The aircraft decelerates when an obstacle is sensed at 49 feet (15 meters) ahead.
- 3. The aircraft stops and hovers then starts ascending vertically to avoid the obstacle. Eventually, the aircraft will stop climbing when it is at least 16 feet (5 meters) above the detected obstacle.
- 4. RTH procedure resumes. The aircraft will continue flying to the Home Point at the current altitude.





\*Coming soon.



- Obstacle Sensing is disabled during RTH descent. Proceed with care.
  - To ensure the aircraft returns home forwards, it cannot rotate during RTH while the Forward Vision System is enabled.
- The aircraft cannot avoid obstacles beside or behind it.

### Landing Protection Function

Landing Protection will activate during auto-landing.

- Landing Protection determines whether the ground is suitable for landing. If so, the Matrice 200 will land smoothly.
- 2. If Landing Protection determines that the ground is not suitable for landing, the Matrice 200 will hover and wait for pilot confirmation. The aircraft will hover if it detects the ground is not appropriate for landing even with a critically low battery warning. Only when the battery level decreases to 0% will the aircraft land. Users retain control of aircraft flight orientation.
- 3. If Landing Protection is inactive, the DJI GO 4 app will display a landing prompt when the Matrice 200 descends below 0.7 meters. Tap to confirm or pull down the control stick for 2 seconds to land when the environment is appropriate for landing.



↑ Landing Protection will not be active in the following circumstances:

- When the user is controlling the pitch/roll/throttle sticks (Landing Protection will re-activate when the control sticks are not in use)
- When the positioning system is not fully functional (e.g. drift position error)
- When the downward vision system needs re-calibration
- When light conditions are not sufficient for the downward vision system
- If an obstacle is within one meter of the aircraft, the aircraft will descend to 0.7m above the ground and hover. The aircraft will land after user confirmation.

### Intelligent Flight Modes

#### TapFlv

### Introduction

With the TapFly feature, users can now tap on the mobile device screen to fly in the designated direction without using the remote controller. The aircraft will automatically avoid obstacles it sees or brake and hover in front of them, provided that there is sufficient light between (< 300 lux) and (> 10,000 lux).


#### Using TapFly

Ensure that the Intelligent Flight Battery is fully charged and the aircraft is in P-mode. Follow the steps below to use TapFly:


1. Take off and ensure the aircraft is hovering at least 6 ft (2 m) above ground.



2. Launch DJI GO 4 and tap , Select TapFly, then follow the prompts.




3. Tap once on the target and wait for the "GO" icon to appear. Tap the "GO" icon to confirm the selection and the aircraft will automatically fly toward the target.




- ↑ DO NOT fly the aircraft over people, animals, small or fine objects (e.g. tree branches and power lines) or transparent objects (e.g. glass or water). TapFly may not work properly when the aircraft is flying over water or snow covered areas.
  - Watch for obstacles in the flight path and steer clear of them.
  - There may be deviations between expected and actual flight paths selected in TapFly.
  - The selectable range for target direction is limited. You cannot make a selection in Direction close to the upper or lower edge of the screen.
  - Be extra cautious when flying in too dark (< 300 lux) or too bright (>10,000 lux) environments.


Enable control stick control of the gimbal inside DJI GO 4 to control gimbal orientation using the remote controller. When using the control sticks, the gimbal will automatically switch to Free mode. In this situation, the control stick used to control pitch on the aircraft now controls gimbal pitch, and the control stick used to control aircraft roll now controls gimbal pan. The left dial now controls flight speed.

After confirming your TapFly selection, the aircraft will fly in the direction marked by the () icon. Note that you can still use the control stick to control the movement of the aircraft during the flight.






The aircraft automatically adjusts its speed when it senses an obstacle in front, or if it flies too close to the ground. The DJI GO 4 app will show a prompt if the aircraft flies over an obstacle or to the left or right of the obstacle. However, this feature should not be relied upon for navigation between obstacles. Failsafe procedures will override TapFly. If the GPS signal weakens, the aircraft will exit autonomous flight and return to home.



### Exit TapFly

Use the following methods to exit TapFly:

- 1. Tap the " I con on the screen.
- 2. Pull back the pitch stick on the remote controller and hold for three seconds or more..
- 3. Press the Intelligent Flight Pause button on the remote controller.



The aircraft will stop and hover after exiting from TapFly. Tap a new target direction to continue flying or begin manual flight.

#### ActiveTrack

ActiveTrack allows you to mark and track a moving object on your mobile device's screen. The aircraft will automatically avoid obstacles in its flight path. No external tracking device is required. The Matrice 200 will automatically identify and trace bicycles and other vehicles, people, and animals, using different tracking strategies for each.


### Using ActiveTrack

Ensure the Intelligent Flight Battery is fully charged and the aircraft is in P Mode. Follow the steps below to use ActiveTrack:


1. Take off and hover at least 6 feet (2 meters) above the ground.



2. In DJI GO 4, tap on to bring up the flight modes and select ActiveTrack.




3. Tap on the subject you want to track, then tap to confirm your selection. If the subject is not automatically recognized, drag a box around it. The box \*\* \*\* will turn green when tracking is in progress. If the box turns red, the object was not identified and you should try again.





ActiveTrack includes the following functions:



Mode. Use this mode in open areas.



- ♠ DO NOT select an area with people, animals, small or fine objects (e.g. trees and power lines), or transparent objects (e.g. glass or water).
  - Stay clear of obstacles near the flight path, particularly when the aircraft is flying backward.
  - Be extra vigilant when using ActiveTrack in any of the following situations:
    - a) The tracked subject is not moving on a level plane.
    - b) The tracked subject changes shape drastically while moving.
    - c) The tracked subject could be blocked or out of sight for a long time.
    - d) The tracked subject is moving on a snowy surface.
    - e) Available light is too low (< 300 lux) or too high (> 10,000 lux).
    - f) The tracked subject has a similar color or pattern as its surrounding environment.
  - You must follow local privacy laws and regulations when using ActiveTrack.
  - Aircraft will not be able to avoid obstacles while in Profile or Spotlight Mode. Use these modes in open areas.

### Exiting ActiveTrack

Use the following methods to exit ActiveTrack:

- 1. Tap the " 

  " button on the screen.
- 2. Press the Intelligent Flight Pause button on the remote controller.





After exiting ActiveTrack, the aircraft will hover in place, at which point you may choose to fly manually, track another subject, or return to home.

### Tripod Mode

Tap the icon in DJI GO 4 to enable Tripod Mode. Tripod Mode reduces the Matrice 200's maximum speed (this can be adjusted in DJI GO 4 app), and the control stick sensitivity of the remote controller is dulled to give you the precision you need for accurate framing. Tripod Mode allow the Matrice 200 to be used as a rocker arm or slide rail, shooting smoother, more stable footage.



Only use Tripod mode when GPS signal is strong or in ideal light conditions for the Vision System. If GPS signal is lost and the Vision System does not function, it will automatically switch to ATTI mode. In this case, flight speed will increase and the aircraft will not hover in place. Use Tripod mode carefully.

### Spotlight Pro


Spotlight Pro is a powerful new tracking mode that allows a single pilot to capture complex, dramatic images. The gimbal will automatically adjust to keep the camera pointing at the subject. Lock onto a subject in Spotlight Pro mode and the gimbal will capture the locked subject regardless of the directions that the aircraft flies.

Quick Mode: Use your finger to draw a square around the object in to begin tracking.

Composition Mode: Use your finger to draw a square. When the subject enters the square, press the C2 button to begin tracking. Press the C2 button again to stop tracking.

In Free mode, you can control the aircraft's heading independently of the camera.

In Follow mode, the aircraft heading will be the same as that of the camera.





- You can drag on a subject in DJI GO 4 or move the gimbal control sticks to change the subject's position in the shot.
- Spotlight Pro can be used in S-mode. A-mode. TapFly and Tripod mode.

### Flight Recorder

Flight data is automatically recorded to the internal storage of the aircraft. This includes flight telemetry, aircraft status information, and other parameters. To access this data, connect the aircraft to a PC via the USB port and launch DJI Assistant 2.

### Attaching and Detaching the Propellers

### Attaching the Propellers

Refer to "Attaching 1550T Quick Release Propellers" for details.

### Detaching the Propellers

Press the propeller down onto the mounting plate and rotate it in the unlock direction.



- Propeller blades are sharp; please handle with care.
- Only use DJI approved propellers. DO NOT mix propeller types.
- Stay clear of spinning motors. DO NOT touch the propellers when they are spinning.
- Ensure to check that the propellers and motors are installed firmly and correctly before each flight.
- Ensure that all propellers are in good condition before each flight. DO NOT use aged, chipped, or broken propellers.
- To avoid injury, stand clear of and DO NOT touch propellers or motors when they are spinning.
- Please use original DJI propellers for a better and safer flight experience.

### DJI Intelligent Flight Battery

The DJI Intelligent Flight Battery has a capacity of 4280 mAh, a voltage of 22.8 V, and a smart charge/discharge functionality. It should only be charged using appropriate DJI approved chargers.


### DJI Intelligent Flight Battery Functions

- 1. Battery Level Display: The LED indicators display the current battery level.
- 2. Auto-Discharging: To prevent swelling, the battery automatically discharges to below 70% of the total power when it is idle (press the power button to check that the battery level will cause the battery to exit idle state) for more than 10 days to prevent swelling. It takes around 3 days to discharge the battery to 65%. It is normal to feel moderate heat emitting from the battery during the discharge process. Discharge thresholds can be set in DJI GO 4.
- 3. Balanced Charging: Automatically balances the voltage of each battery cell when charging.
- 4. Overcharge Protection: Charging automatically stops when the battery is fully charged.
- 5. Temperature Detection: The battery will only charge when the temperature is between 5 °C (41°F) and 45°C (113°F).
- Over Current Protection: The battery stops charging when a high amperage (more than 10 A) is detected
- 7. Over Discharge Protection: Over-discharging can seriously damage the battery. Current output will be cut off when the battery cell is discharged to 2.8 V when not in flight mode. For extended flight times, over-charging protection is disabled as batteries discharge during flight. In this instance, a battery voltage below 2 V may cause a safety hazard such as a fire when charged. To prevent this, the battery will not be able to charge if the voltage of a single battery cell is below 2 V. Avoid using any batteries matching this description and avoid serious over-discharging to prevent permanent battery damage.
- 8. Short Circuit Protection: Automatically cuts the power supply when a short circuit is detected.
- Battery Cell Damage Protection: DJI GO 4 displays a warning message when a damaged battery cell is detected.
- 10. Sleep Mode: Sleep mode is entered to save power when the aircraft is not flying.
- 11. Communication: Information pertaining to the battery's voltage, capacity, current, etc. is transmitted to the aircraft's main controller.
- 12. Pairing Batteries: Powered by two batteries (with battery cells connected in parallel), the Matrice 200 requires the two batteries to have similar properties, e.g. internal resistance. Pairing batteries in the beginning is recommended. Pairing can be done using DJI GO 4. DJI GO 4 will also prompt you when batteries that are not paired are not in use. The Intelligent Flight Battery Charging Hub will charge paired batteries simultaneously. Stickers are provided for marking paired batteries.
- 13. Heating: Batteries are able to work even in cold weather, ensuring a safe flight. Refer to "Using the Battery" section for details.
- 14. Waterproof and Dustproof: The vehicle's new airframe design improves the Ingress Protection Rating to IP43 in accordance with the global IEC 60529 standards.
- Refer to the *Disclaimer* and *Intelligent Flight Battery Safety Guidelines* before use. Users take full responsibility for all operations and usage.

### Charging the Intelligent Flight Battery

The Matrice 200 Intelligent Flight Battery Charging Hub is designed for use with the Matrice 200 Battery Charger. It charges up to four Intelligent Flight Batteries simultaneously. The battery pair with more stored power will be charged first. The Charging Hub will intelligently charge batteries in sequence according to battery power levels from high to low, if batteries are not paired. Pairing can be carried out using the DJI GO 4 app. The Micro USB port is used for firmware updates.


#### Overview



- [1] Power Port
- [2] Charging Port
- [3] Charging Port Cover
- [4] Battery Charging Level Indicators
- [5] Cover/Battery Release Button
- [6] Status LEDs
- [7] Firmware Update Port (Micro USB)
- [8] Buzzer Switch

#### Connecting to a Power Source


Connect the standard Matrice 200 Battery Charger to a power outlet (100-240 V, 50/60 Hz), then uncover the rubber cover on the power port to connect the Charging Hub to the Matrice 200 Battery Charger\*.



\* It will take approximately 1.5 hours to fully charge the Matrice 200 Intelligent Flight Battery, and 3 hours for the remote controller. It will take a longer time to charge the Intelligent Flight Battery and remote controller together.

### **Connecting Batteries**

Press the release button and open the corresponding charging port cover. Insert the Intelligent Flight Battery into the charging port to begin charging. The battery pair with more stored power will be charged first. The Charging Hub will intelligently charge batteries in sequence according to battery power levels from high to low, if batteries are not paired. Pairing can be carried out using the DJI GO 4 app. Refer to the "Status LED Description" section for more information about Status LED blinking patterns. The buzzer will begin beeping when charging is complete. Refer to the "Buzzer Beeping Description" for more information about buzzer beeping patterns.





- Always align the grooves on the Intelligent Flight Battery with the battery slot tracks.
- Press the release button to detach batteries after charging is complete.
- DO NOT leave metal terminals exposed to open air when not in use.

### Status LED Descriptions

Status	LED (Charging Hub)	Description
Ğ	Blinks Green	Charging
· · · · · ·	Solid Green	Fully charged
®	Blinks Red	Battery Charger Error. Retry with an official battery charger.
® —	Solid Red	Intelligent Flight Battery error
· · · · · · · · · · · · · · · · · · ·	Blinks Yellow	Battery temperature too high/low. Temperature must be within operating range (5°-40°C)
<b>:</b>	Solid Yellow	Ready to charge
·	Alternating Green Blinks	Intelligent Flight Battery not detected

Battery Level Indicators while Charging (Battery)					
LED1	LED2	LED3	LED4	Battery Level	
<del>-</del> ;Ö:-	-Ö:	0	0	0%~50%	
÷);;;	Ö:	:Ö:	0	50%~75%	
-);	-Ö:	:Ö:	- <u>;</u> \(\);	75%~100%	
0	0	0	0	Fully Charged	

### Charging Protection LED Display

The table below shows battery protection mechanisms and corresponding LED patterns.

Battery	Battery Level Indicators for Battery Protection					
LED1	LED2	LED3	LED4	Blinking Pattern	Battery Protection Item	
$\circ$	- <u>;</u> ;;	0	0	LED2 blinks twice per second	Over current detected	
0	÷Ö÷	0	0	LED2 blinks three times per second	Short circuit detected	
$\circ$	0	:Ö:	0	LED3 blinks twice per second	Over charge detected	
0	0	÷Ö÷	0	LED3 blinks three times per second	Over-voltage charger detected	
0	0	0	:Ö:	LED4 blinks twice per second	Charging temperature is too low (<0°C)	
0	0	0	:Ö:	LED4 blinks three times per second	Charging temperature is too high (>40°C)	

After any of the above mentioned protection issues are resolved, press the button to turn off the Battery Level Indicator. Unplug the Intelligent Flight Battery from the charger and plug it back in to resume charging. Note that you do not need to unplug and plug the charger in the event of a room temperature error, the charger will resume charging when the temperature falls within the normal range.



DJI does not take any responsibility for damage caused by third-party chargers.



How to discharge the Intelligent Flight Battery before transporting the batteries for a trip:

Fly the aircraft outdoors until there is low battery power left, or until the battery can no longer be turned on.

### **Buzzer Beeping Description**

Toggle the buzzer switch to turn on/off the warning sound.

Descriptions	Beeping Pattern
Toggle the buzzer switch to turn it on	Quick beeping
Connect to the Battery Charger	Quick beeping
A battery pair is fully charged	Quick beeping
Four Intelligent Flight Batteries are fully charged	Alternating between two short and one long beep, lasting for about 1 hour

### Updating the Firmware

DJI will release firmware updates when available. Refer to the official DJI website and follow the instructions below to update the firmware.

- Download the latest firmware update program from the official DJI website. (http://www.dji.com/matrice-200-series/info#downloads)
- 2. Turn on the Charging Hub, then connect it to a computer using a Micro USB cable.



- 3. Run the firmware update program. Press the update button and wait for the process to finish.
- 4. The Charging Hub will automatically restart when the update has been successfully completed.
- 5. Repeat this process if the firmware update fails for any reason.

### Using the Battery





### Turning ON/OFF

Turning On: Press the Power button once, then press again and hold for two seconds to power on.

The Power LED will turn red and the Battery Level Indicators will display the current

battery level.

Turning Off: Press the Power button once, then press again and hold for two seconds to power off.

### Heating the Battery

Manual Heating: Make sure the battery is powered off. Press and hold the Power button for three seconds to initiate battery warm up manually.

The battery will warm up if the temperature is below 59°F (15°C). As it warms, LEDs 1 & 2 and LEDs 3 & 4 will blink alternately. The battery will stop warming when it reaches 68°F (20°C). The temperature of the battery will be remain between 59-68°F (15-20°C) when alternating LED 1 and LED 4 blinking indicates that it is above 59°F (15°C). This will last for approximately 30 minutes, powering off automatically.

Auto Heating: Insert the batteries into the aircraft and power it on. When the temperature of the battery is below 59°F (15°C), it will warm up automatically. Check the LEDs for the current power level.

#### Low Temperature Notice:

- The performance of the intelligent Flight Battery is significantly reduced when flying in low temperature environments (temperatures below 5°C). Ensure that the battery is fully charged and the cell voltage is at 4.35 V before each flight.
- End the flight as soon as DJI GO 4 displays the "Low Battery Level Warning" in low temperature environments. You will still be able to control the aircraft's movement when this warning is triggered.
- 3. In extremely cold weather, the battery temperature may not be high enough even after warming up. In these cases, insulate the battery as required.
- 4. To ensure optimal performance of the battery, keep the battery temperature above 15°C.
- 5. Battery insulation paste is available for you to use.

#### Checking Battery Levels

Battery Level Indicators display how much power remains. When the battery is turned off, press the Power button once and the Battery Level Indicators LEDs will display the current battery level. See below for details.

The Battery Level Indicators will also show the current battery level during discharging. The indicators are defined below.

: LED is off.

Battery Level					
LED1	LED2	LED3	LED4	Battery Level	
				88%~100%	
			÷;;;-	75%~88%	
				63%~75%	
		÷;;;-		50%~62.5%	
				38%~50%	
	- 🗮 -	0		25%~38%	
				13%~25%	
->	0	0	0	0%~13%	

## **Remote Controllers**

This section describes the features of the remote controller that includes aircraft and remote controller operations and dual remote controller mode.



# **Remote Controller**

# Remote Controller Profile

The Matrice 200 remote controller is a multi-function wireless communication device that integrates a dual frequency video downlink system and the aircraft remote control system. 2.4 GHz frequency is suitable for long transmission distances in open areas while 5.8 GHz frequency\* is appropriate for urban areas, being resistant to increased interference (5.8 GHz transmission is not available in some regions due to local regulations). The remote controller features many camera control functions, including photo/video capture and gimbal control. The battery level is displayed via LED indicators on the front panel of the remote controller. When in Dual Remote Controller mode, each of the two remote controllers will control aircraft and camera separately, and up to 328 feet (100 meters) apart.



- Compliance Standards: The remote controller is compliant with local laws and regulations.
  - Stick Mode: Controls can be set to Mode 1, Mode 2, or to a custom mode.
  - Mode 1: The right stick serves as the throttle.
  - Mode 2: The left stick serves as the throttle.




Do not operate more than three aircraft within the same area (roughly the size of a soccer field) to prevent transmission interference.

# Remote Controller Operations

## Turning the Remote Controller On and Off

The Matrice 200 remote controller is powered by a 2S rechargeable battery with a capacity of 6000 mAh. The battery level is indicated by Battery Level LEDs on the front panel.


- 1. When powered off, press the Power button once and the Battery Level LEDs will display the current battery level.
- 2. Next, press and hold the Power button to power on the remote controller.
- 3. The Remote Controller will beep when it powers on. The Status LED will blink green and the slave remote controller will blink solid purple rapidly, indicating that the remote controller is linking to the aircraft. The Status LED will show a solid green light when linking is complete.
- 4. Repeat step 2 to power off the remote controller after you finish using it.



<sup>\*</sup> To comply with local regulations, the operation frequency of 5.8GHz is not available in some countries.

# Charging the Remote Controller

Charge the remote controller via the supplied charger.



## Controlling the Camera

Shoot videos/photos and adjust the camera settings via the Shutter Button, Camera Settings Dial, Video Recording Button, and Gimbal Dial on the remote controller.



#### [1] Camera Settings Dial

Turn the dial to adjust camera settings such as ISO, shutter speed, and aperture without letting go of the remote controller. Press down on the dial to toggle between these settings.

## [2] Shutter Button

Press to take a photo. If Burst mode is activated, multiple photos will be taken with a continuous press. Press to take a photo even when recording.

#### [3] Video Recoding Button


Press once to start recording video, then press again to stop recording.

## [4] Gimbal Dial

Control the tilt of the gimbal.

# Controlling the Aircraft

This section explains how to control the orientation of the aircraft through the remote controller. Control can be set to Mode 1, Mode 2 or Mode 3, or to a custom mode.



The Stick Mode is set to Mode 2 by default.

Stick Neutral/Mid-Point: Control sticks are centered.

Moving the Control Stick: Control sticks are pushed away from the center.


Turn Right

Turn Left

Remote Controller (Mode 2)	Aircraft ( ● indicates nose direction)	Remarks
		Moving the left stick up and down changes the aircraft's elevation.  Push the stick up to ascend and down to descend.  When both sticks are centered, the Matrice 200 will hover in place.  The more the stick is pushed away from the center position, the faster the Matrice 200 will change elevation. Always push the stick gently to prevent sudden and unexpected elevation changes.
6		Moving the left stick to the left or right controls the rudder and rotation of the aircraft.  Push the sick left to rotate the aircraft counter clockwise, and push the stick right to rotate the aircraft clockwise. If the stick is centered, the Matrice 200 will maintain its current orientation.  The more the stick is pushed away from the center position, the faster the Matrice 200 will rotate.
		Moving the right stick up and down changes the aircraft's forward and backward pitch. Push the stick up to fly forward and down to fly backward. The Matrice 200 will hover in place if the stick is centered. Push the stick further away from the center position for a larger pitch angle and faster flight.
	\$\dagger\$	Moving the right stick control left and right changes the aircraft's left and right pitch.  Push left to fly left and right to fly right. The Matrice 200 will hover in place if the stick is centered.  Push the stick further away from the center position for a larger pitch angle and faster flight.
		Gimbal Dial: Turn the dial to the right, and the camera will shift to point upwards. Turn the dial to the left, and the camera will shift to point downwards. The camera will remain in its current position when the dial is static.
		Press the Intellighent Flight Pause button to pause the current task.

# Adjusting Controller Sticks


Hold and twist the controller sticks clockwise or counter clockwise to adjust their height. A proper length of controller sticks can improve the controlling accuracy.



## Flight Mode Switch

Toggle the switch to select the desired flight mode. Choose between; P-mode, S-mode, and A-mode.

Position	Figure	Flight Mode
Position 1	B	P-mode
Position 2	<b>b</b>	S-mode
Position 3	B	A-mode



P-mode (Positioning): P-mode works best when the GPS signal is strong. The aircraft utilizes GPS, stereo Vision Systems, and an Infrared Sensing System to stabilize, avoid obstacles or track moving subjects. Advanced features such as TapFly and ActiveTrack are enabled in this mode.

S-mode (Sport): The handling gain values of the aircraft are adjusted to enhance aircraft maneuverability. Note that Obstacle Sensing systems are disabled in this mode.

**A-mode (Attitude):** When neither the GPS nor the Vision System is available, the aircraft will only use its barometer for positioning to control the altitude.

The Flight Mode Switch is locked to P-mode, regardless of the Flight Mode Switch's position. To change flight modes, go to the Camera View in DJI GO 4 and enable Multiple Flight Modes in Main Controller Settings. After enabling multiple flight modes, toggle the switch to P for Position mode and S for Sport Mode.

#### **RTH Button**

Press and hold the RTH button to start the Return to Home (RTH) procedure. The aircraft will then return to the last recorded Home Point. Press this button again to cancel the RTH procedure and regain control of the aircraft.

Determine RTH status by sound:

Single beep... Request to return, but not receive the respond from the aircraft yet.

Double beep... RTH in progress.




# Connecting Your Mobile Device

Tilt the Mobile Device Holder to the desired position. Press the button on the side of the Mobile Device Holder to release the clamp, then place your mobile device into the clamp. Adjust the clamp to secure your mobile device. Connect your mobile device to the remote controller with a USB cable. Plug one end of the cable into your mobile device and the other end into the USB port on the back of the remote controller.



# Optimal Transmission Range

The transmission signal between the aircraft and the remote controller is most reliable when the antennas are positioned in relation to the aircraft as depicted below:



Ensure the aircraft is flying within the optimal transmission zone. To maintain optimal transmission performance, adjust the remote controller and antennas according to the above diagram. The position of the antennas required for optimal transmission range varies in the frequency of 5.8 GHz and 2.4 GHz. Please place the antennas based on the actual operating frequency.

# **Dual Remote Controller Mode**

More than one remote controller can connect to the same aircraft in Dual Remote Controller mode. The Master remote controller operator controls the orientation of the aircraft, while the Slave remote controller controls the movement of the gimbal and camera operation. Master and Slave remote controllers communicate each other via Wi-Fi.




- In Dual Controller Mode, when the Master remote controller is primary, it can control gimbal pitch and pan. When the Slave remote controller is primary, it can control gimbal pitch, pan, and roll.
- Dual Remote Controller mode is not available in Russia and Israel.

# Setting Up Dual Remote Controller Mode

Dual Remote Controller mode is disabled by default. Users must enable this feature on the Master remote controller via DJI GO 4. Follow the steps below to setup:


#### Master Remote Controller:

- 1. Connect the remote controller to your mobile device and launch DJI GO 4.
- 2. Go to the Camera View and tap in to enter the remote controller settings window.
- 3. Select Master and set the remote controller as the Master remote controller.
- 4. Enter the connection password for the Slave remote controller.



#### "Slave" Remote Controller:


1. Select Slave to set the remote controller to Slave.




 $\triangle$ 

When in Slave, the remote controller cannot link to the aircraft nor control aircraft orientation. Select Master in DJI GO 4 if you wish to connect and control the aircraft with the remote controller.

2. Search the "Master" remote controller in the surrounding area.




3. Select the Master remote controller from the Master list and input the password to connect.



# Remote Controller Status LED

The Status LED displays the connection status between the remote controller and aircraft. The RTH LED displays the Return to Home status of the aircraft. See the table below for details.




Status LED	Alarm	Remote Controller Status
® — Solid Red		The remote controller is set as Master but is not connected with the aircraft.
© — Solid Green		The remote controller is set as Master and is connected with the aircraft.
© — Solid Purple		The remote controller is set as Slave but is not connected with the aircraft.
® — Solid Blue	_	The remote controller is set as Slave and is connected with the aircraft.
® ······ Slow Blinking Red	D-D-D	Remote controller error.
RTH LED	Sound	Remote Controller Status.
Solid White	♪ chime	Initiates RTH procedure.
: Winking White	$D\cdots$	Sends RTH command to aircraft.
Wite Blinking White	DD	Aircraft is returning to the Home Point.

The Remote Status Indicator will blink red and sound an alert when the battery level is critically low.


# Linking the Remote Controller

The remote controller comes linked to your aircraft before delivery. Linking is only required when using another remote controller for the first time. Follow these steps to link a remote controller:

- 1. Power on the remote controller, connect to your mobile device, and launch DJI GO 4.
- 2. Power on the Intelligent Flight Battery.
- 3. Enter Camera View and tap the Linking Remote Controller button shown below.



- 4. The remote controller is ready to link. The Remote Controller Status Indicator blinks blue, and a "beep" sound is emitted.
- Locate the Linking button on the aircraft, as shown in the figure shown below. Press the Linking button to start linking. The Remote Controller Status Indicator will display solid green if the connection is successful.






- A Slave remote controller cannot link to the aircraft and so therefore cannot control the orientation of the aircraft. Select Master in DJI GO 4 if you wish to link a remote controller it to the aircraft.
- A remote controller will disconnect from the linked aircraft if a new remote controller is linked to the same aircraft.
- Press the C1 and C2 buttons and the Start/Stop button for fast linking.

# **Gimbal and Camera**

This section focuses on the technical specifications of the camera and explains how to use the gimbal.



# Camera and Gimbal


# Camera

#### Camera Profile

Using the Zenmuse Z30 as an example, this section will demonstrate the technical specifications of the camera while explaining how to use the gimbal.

#### Camera Micro SD Card Slot

To store photos and videos, plug the Micro SD card into the slot shown below before powering on the Matrice 200. The Matrice 200 comes with a 16 GB Micro SD card and can support card sizes of up to 128 GB. We recommend you use a UHS-3 type Micro SD card because the fast read and write capability of these cards enables you to store high-resolution video data.




- The Matrice 200 currently supports the following Micro SD cards, and will continue to support more cards in future.
  - SanDisk Extreme 32GB UHS-3 microSDHC
  - SanDisk Extreme 64GB UHS-3 microSDXC
  - Panasonic 32GB UHS-3 microSDHC
  - Panasonic 64GB UHS-3 microSDXC
  - Samsung PRO 32GB UHS-3 microSDHC
  - Samsung PRO 64GB UHS-3 microSDXC
  - Samsung PRO 128GB UHS-3 microSDXC



- Do not remove Micro SD card from the Matrice 200 when it is powered on.
- To ensure the stability of the camera system, single video recordings are capped at 30 minutes.

## **USB Port**

Power on the Matrice 200 and then connect a USB cable to the USB port to download photos or videos from the Matrice 200 to your computer.



Power on the aircraft before attempting to download the files.

# Camera Operation

#### Remote Controller

Use the Shutter and Record buttons on the remote controller to shoot photos or videos. For more information on how to use these buttons, please refer to Controlling the Camera.


#### DJI GO 4

Use DJI GO 4 to shoot photos or videos. For more information, refer to the camera and gimbal User Manual.

# Gimbal

#### Gimbal Profile


The 3-axis gimbal provides a steady platform for the attached camera, allowing you to capture stabilized images and video.



## Using the DJI GO 4 App to Control Gimbal


Follow the steps below to use the DJI GO 4 app to control gimbal orientation:

- 1. Launch DJI GO 4 and enter the Camera View.
- 2. Tap and press on the screen until a blue circle is shown.
- 3. Slide to control the gimbal's orientation within the Camera View as shown below.



# Gimbal Operation Modes

Three gimbal operation modes are available. Switch between the different operation modes in DJI GO 4's Camera View. Note that your mobile device must be connected to the remote controller for changes to take effect. Refer to the table below for details:



4	Follow Mode	Gimbal pan cannot be controlled in this mode.
A	Free Mode	The Gimbal's motion is independent of the aircraft's orientation.
10	Reset	Tap and the gimbal will pan to realign with the aircraft's nose. The tilt angle will remain unchanged during re-alignment.


- $\triangle$
- Gimbal pan cannot be controlled in Follow Mode. In Free Mode, press and hold the C1 Button while rotating the control dial to adjust gimbal yaw.
- The gimbal will be in free mode when the Slave remote controller controls the gimbal in Dual Remote Controller Mode.

# DJI GO 4

This section introduces the main functions of the DJI GO 4 app.

# DJI GO 4

Use the DJI GO 4 app to control the gimbal, camera, and other aircraft functions. The app features Equipment, Editor, SkyPixel, and Me sections, which are used for configuring your aircraft, editing, and sharing your photos and videos with others. It is recommended that you use a tablet for the best possible experience.




Both DJI GO 4 and DJI Pilot support the Zenmuse X5S, X4S, and Z30. DJI Pilot is required if using the Zenmuse XT. This manual uses DJI GO 4 as an example. Please refer to the actual user interface.

# Equipment

Enter the Camera View by tapping the GO FLY icon on the Equipment page when your mobile device is connected to the aircraft.

#### Camera View



#### 1. System Status

PREADY TO GO (GPS): This icon indicates aircraft flight status and displays various warning messages.

## 2. Battery Level Indicator

→ • The battery level indicator provides a dynamic display of the battery level. The colored zones on the battery level indicator represent the power levels needed to carry out different functions.

## 3. Flight Mode

**X**: The text next to this icon indicates the current flight mode.

Tap to configure the Flight Controller Settings. These settings allow you to modify flight limits and set gain values.

#### 4. Camera Parameters

Displays camera settings parameters and capacity of the Micro SD card.



- (1) Tap sook to set white balance parameters.
- (2) Tap 4KP30 20:12 to set photo and video parameters.

## 5. AirSense Status

(a): AirSense Status displays information about nearby manned aircraft to ensure flight safety, including the distance between DJI aircraft and manned aircraft. AirSense will instruct users to land if nearby aircraft are detected.



## 6. GPS Signal Bars

الله: Shows current GPS signal strength. Four GPS signal bars indicates sufficient GPS strength to return to home.

#### 7. Obstacle Sensing Function Status

•i)): Tap this icon to enable or disable features provided by the Vision System.

# 8. Remote Controller Signal Bars

: This icon shows the strength of the remote controller signal.

## 9. HD Video Link Signal Bars

HD<sub>nll</sub>: This icon shows the strength of the HD video downlink connection between the aircraft and remote controller.

#### 10. Focus/Metering Button

[ ] / (•): Tap to switch between the focus and metering modes. Tap to select an object for focusing or metering.

#### 11. Battery Level

1 74% 4.07V : This icon shows current battery level.

Tap to view the battery information menu, set various battery warning thresholds, and view battery warning history.

## 12. General Settings

•••: Tap to enter the General Settings menu to set metrics to enable live streaming, display flight routes, and so on.

#### 13. AF/MF

AF/MF: Tap to switch the focus mode.

### 14. Auto Exposure Lock

♠ AE : Tap to lock the exposure value.

## 15. Photo/Video Toggle

: Tap to switch between photo and video recording modes.

## 16. Gimbal Slider

• Displays the pitch of the gimbal.

#### 17. Shoot / Record Button

/ ① : Tap to start shooting photos or recording video.

#### 18. Camera Settings

∴ Tap to set ISO, shutter and auto exposure values of the camera.

#### 19. Playback

► Tap to enter the playback page and preview photos and videos as soon as they are captured.

#### 20. Manual Focus

Only effective in MF mode.

## 21. FPV

FPV is only available on tablets. Pinch to zoom in or out of the window.



: Red bars are displayed when obstacles are close to the aircraft. Orange bars are displayed when obstacles are in detection range.

Tap to zoom in on the FPV window and move it to the middle of the screen.

#### 22. Flight Telemetry



**30**m **H 10.0**m **H.S** 10.0km/h **VS** 2.0m/s

VPS 2.0m

- (1) Tap to switch to map view.
- (2) Flight Attitude and Radar Function:



- The red arrow shows which direction the aircraft is facing.
- The ratio of gray area to blue area indicates the aircraft's pitch.
- The horizontal level of the gray area indicates the aircraft's roll angle.
- A blue line indicates the current position of the gimbal's tilt motor.
- The outermost gray circle displays the current power capacity.

## (3) Flight Parameters:

Altitude: Vertical distance from the Home Point.
Distance: Horizontal distance from the Home Point.
Vertical Speed: Movement speed across a vertical distance.
Horizontal Speed: Movement speed across a horizontal distance.

#### (4) Aircraft Distance:

The horizontal distance between the aircraft and the operator.

#### 23. Spotlight Pro

(1): Tap to use the Spotlight Pro function.

#### 24. Intelligent Flight Mode

(in): Displays the current mode. Tap to select Intelligent Flight Mode.

#### 25. Smart RTH

&: Initiate RTH procedure. Tap to have the aircraft return to the last recorded home point.

#### 26. Gimbal Working Modes

Follow mode, free mode and reset mode are included.

#### 27. Auto Takeoff/Landing

📤 🕭 : Tap to initiate auto takeoff or landing.

## 28. Livestream

②: This icon indicates that the current video feed is being broadcast live on YouTube. Ensure a mobile data service is available on your mobile device.

## 29. Back

: Tap this icon to return to the main menu.

# Editor

A dedicated video editor is built into the DJI GO 4 app. After recording several video clips and downloading them to your mobile device, go to Editor on the home screen. You can then select a template and a specified number of clips that automatically combine, creating a short film for sharing.

# SkyPixel

View and share photos and videos on the SkyPixel page.

# Me

If you already have a DJI account, you will be able to participate in forum discussions, and share your creations with the community.

# Flight

This section describes safe flight practices and flight restrictions.



# **Flight**

Ensure that all flights are carried out in an open area. It is important to understand basic flight guidelines for the safety of both you and those around you. Refer to the Disclaimer and Safety Guidelines for more information.

# Flight Environment Requirements

- Do not use the aircraft in severe weather conditions. These include wind speeds exceeding 10 m/s. snow, rain, and fog.
- When flying in open areas, tall and large metal structures may affect the accuracy of the onboard compass and GPS system.
- 3. Avoid obstacles, crowds, high voltage power lines, trees, and bodies of water.
- Minimize interference by avoiding areas with elevated levels of electromagnetism, including base stations and radio transmission towers.
- Aircraft and battery performance is subject to environmental factors such as air density and temperature. Be very careful when flying at high altitudes, as battery and aircraft performance may be affected.
- The compass and GNSS will not work in Polar Regions. The aircraft will have to auto switch to A-mode, using the Vision System for positioning.


# Flight Limits and No-Fly Zones

All unmanned aerial vehicle (UAV) operators should abide by all regulations set forth by government and regulatory agencies including the ICAO and the FAA. For safety reasons, flights are limited by default, which helps users operate this product safely and legally. Flight limitations include height limits, distance limits, and No-Fly Zones.

When operating in P-mode, height limits, distance limits, and No-Fly Zones function concurrently to manage flight safety. In A-mode, only height limits are in effect, which by default prevent the aircraft altitude from exceeding 1640 feet (500 m).

## Maximum flight altitude & Radius Limits

Maximum flight altitude and radius limits may be changed in the DJI GO 4 app. Be aware that the maximum flight altitude cannot exceed 1640 feet (500 meters). In accordance with these settings, your Matrice 200 will fly in a restricted cylinder, as shown below:



GPS Signal Strong 6 ······ Blinking Green			
	Flight Limits	DJI GO 4 App	
Maximum Flight Altitude	Aircraft's altitude cannot exceed the specified value.	Warning: Height limit reached.	
Max Radius	Flight distance must be within the max radius.	Warning: Distance limit reached.	

GPS Signal Weak 💯 · · · · · Blinking Yellow			
	Flight Limits	DJI GO 4 App	
Maximum Flight Altitude	Height is restricted to 26 feet (8 meters) when the GPS signal is weak and Vision Positioning is active. Height is restricted to 98 feet (30 meters) when the GPS signal is weak and Vision Positioning is inactive.	Warning: Height limit reached.	
Max Radius	No Limits		



- If the aircraft flies out of the limit, you can still control the aircraft, but you cannot fly it any farther.
- If the aircraft flies out of the max radius it will fly back within range automatically when GPS signal is strong.
- For safety reasons, please do not fly close to airports, highways, railway stations, railway lines, city centers, or other sensitive areas. Fly the aircraft only within your line of sight.


#### No-Fly Zones

All No-Fly Zones are listed on the DJI official website at http://www.dji.com/flysafe/no-fly. No-Fly Zones are divided into Airports and Restricted Areas. Airports include major airports and flying fields where manned aircraft operate at low altitudes. Restricted Areas include country borders or locations where flights may cause security concerns. The details of the No-Fly Zones are explained below:

#### Airport:


- (1) Airport No-Fly Zones comprise of Takeoff Restricted Zones and Restricted Altitude Zones. Each zone features circles of various sizes.
- (2) R1 miles depends on the shape and size of the airport and is an area around the airport that is a Takeoff Restricted Zone, within which takeoff and flight are prohibited.
- (3) From R1 mile to R1 + 1 mile around the airport the flight altitude is restricted to a 15-degree inclination, starting at 65 feet (20 meters) from the edge of the airport and radiating outward. Flight altitude is limited to 1640 feet (500 meters) at R1+1 mile.

(4) When the aircraft flies within 320 feet (100 meters) of a No-Fly Zone, a warning message will appear in DJI GO 4.



#### Restricted Areas:

- (1) Restricted Areas do not have flight altitude restrictions.
- (2) R miles around the designated restriction area is a Takeoff Restricted area. Aircraft cannot take off within this zone. The value of R varies based on the definition of the restricted areas.
- (3) A "warning zone" has been set around the Restricted Area. When the aircraft approaches within 0.062 miles (100 m) of this zone, a warning message will appear in DJI GO 4.



- ⚠
- When flying in a safety zone, the aircraft's status indicator will blink red rapidly and continue for three seconds, then switch to indicate current flying status and continue for five seconds at which point it will switch back to blinking red.
- For safety reasons, please do not fly close to airports, highways, railway stations, railway lines, city centers, or other sensitive areas. Fly the aircraft only within your line of sight.

# **Preflight Checklist**

- 1. Remote controller, Intelligent Flight Battery, and mobile device are fully charged.
- 2. Propellers are mounted correctly and firmly.
- 3. Micro SD card has been inserted, if necessary.
- 4. Gimbal is functioning normally.
- 5. Motors can start and are functioning normally.
- 6. The DJI GO 4 app is successfully connected to the aircraft.
- 7. Ensure that the sensors for the Obstacle Sensing System are clean.

# Calibrating the Compass

Only calibrate the compass when the DJI GO 4 app or the status indicator prompts you to do so. Observe the following rules when calibrating your compass:



- DO NOT calibrate your compass where there is a chance of strong magnetic interference, such as near magnets, parking structures, or steel reinforcements underground.
- DO NOT carry ferromagnetic materials with you during calibration such as cellular phones.
- The DJI GO 4 app will notify you if the compass is affected by strong interference after calibration is complete. Follow the prompts to resolve the compass issue.


#### Calibration Procedures

Choose an open area to carry out the following procedures.

- 1. Tap the Aircraft Status Bar in the app and select Calibrate, then follow the on-screen instructions.
- Hold the aircraft horizontally and rotate it 360 degrees. The Aircraft Status Indicators will go solid green.



Hold the aircraft vertically, with the nose pointing downward, and rotate it 360 degrees around the center axis. Re-calibrate the aircraft if the aircraft status indicators blink red.





If the Aircraft Status Indicator blinks red and yellow after the calibration procedure, move your aircraft to a different location and try again.



- DO NOT calibrate the compass near metal objects such as a metal bridge, cars, scaffolding.
- If the aircraft status indicators are blinking red and yellow alternately after placing the aircraft on the ground, the compass has detected magnetic interference. Please change your location.

# Auto Takeoff and Auto Landing

#### Auto Takeoff

Use auto takeoff only if the Aircraft Status Indicators are blinking green. Follow the steps below to use the auto takeoff feature:

- 1. Launch the DJI GO 4 app and tap GO FLY to enter Camera View.
- 2. Complete all steps on the pre-flight checklist.
- 3. Tap" (\$\frac{1}{2}\), and confirm that conditions are safe for flight. Slide the icon to confirm and takeoff.
- 4. Aircraft takes off and hovers at (1.2 meters) above ground.



Aircraft Status Indicator blinks rapidly when it is using the Vision System for stabilization. The aircraft will automatically hover below 10 meters. It is recommended to wait until there is sufficient GPS lock before using the Auto Takeoff feature.

# Auto-Landing

Use auto-landing only if the Aircraft Status Indicator is blinking green. Follow the steps below to use the auto-landing feature:

- 1. Tap 🔥, to ensure that landing conditions are ideal. Slide to confirm.
- 2. Abort landing process immediately by tapping  $\otimes$  on the screen.

- 3. a. When Landing Protection determines that the ground is suitable for landing, the Matrice 200 will land gently.
  - b. If Landing Protection determines that the ground is not suitable for landing, the Matrice 200 will hover and wait for pilot confirmation.
  - c. If Landing Protection is not operational, the DJI GO 4 app will display a landing prompt when the Matrice 200 descends below 0.7 meters. Pull down on the throttle or use the auto landing slider to land.
- 4. The aircraft will land and turn off automatically.

# Starting/Stopping the Motors

## Starting Motors

The Combination Stick Command (CSC) is used to start the motors. Push both sticks to the bottom inner or outer corners to start the motors. Once the motors start spinning, release both sticks simultaneously.





OR





## Stopping the Motors

There are two ways to stop the motors:

- 1: When Matrice 200 has landed, push the left stick down ①, then conduct the same CSC that was used to start the motors, as shown above ②. Motors will stop immediately. Release both sticks once motors stop.
- 2: When the aircraft has landed, push and hold the left stick down. The motors will stop after three seconds.











Method 1

OR








Method 2

# Stop the Motor Mid-flight

Pull the left stick to the bottom right inside corner and press the RTH button at the same time. **Only stop** the motors mid-f light in emergency situations when doing so reduces the risk of damage or injury.



Please check that CSC is activated inside DJI GO 4 app, then the user can stop the aircraft mid-air.

# Flight Test

## Takeoff/Landing Procedures

- 1. Place the aircraft in an open, flat area with the battery level indicators facing towards you.
- 2. Turn on the remote controller and your mobile device, then turn on the Intelligent Flight Battery.
- 3. Launch DJI GO 4 and enter the Camera View.
- 4. Wait until the Aircraft Indicators blink green. This means the Home Point has been recorded and it is now safe to fly. If they flash yellow, the Home Point has not been recorded.
- 5. Turn on the motors using CSC and push the left stick up slowly or use Auto Takeoff to take off.
- 6. Shoot photos and videos using the DJI GO 4 app.
- 7. To land, hover over a level surface and gently pull down on the left stick to descend.
- After landing, execute the CSC command or hold the left stick at its lowest position until the motors stop.
- 9. Turn off the Intelligent Flight Battery first, then the remote controller..



- When the Aircraft Status Indicators blink yellow rapidly during flight, the aircraft has entered Failsafe mode.
- A low battery level warning is indicated by the Aircraft Status Indicators blinking red slowly
  or rapidly during flight.
- Watch our video tutorials for more flight information.

## Video Suggestions and Tips

- 1. Go through the full pre-flight checklist before each flight.
- 2. Select the desired gimbal operation mode in the DJI GO 4 app.
- 3. Only shoot video when flying in P-mode.
- 4. Always fly in good weather and avoid flying in rain or heavy wind.
- Choose the camera settings that suit your needs. Settings include photo format and exposure compensation.
- 6. Perform flight tests to establish flight routes and preview scenes.
- 7. Push the control sticks gently to keep the aircraft's movement smooth and stable.



- It is important to understand basic flight guidelines for the safety of both you and those around you.
- Refer to the Disclaimer and Safety Guidelines for more information.

# **Appendix**

# **Appendix**

# Specifications

Aircraft			
Model	M200		
Dimensions	Unfolded, 887×880×378 mm		
Differsions	Folded, 716×220×236 mm		
Diagonal Wheelbase	643 mm		
Max Takeoff Weight	6.14 kg		
Max Payload	<ul><li>2.34 kg (with two standard batteries ),</li><li>1.61 kg (with two optional batteries)</li></ul>		
Hovering Accuracy (P-mode with GPS)	Vertical: ±1.64 feet (0.5 m) or ±0.33 feet (0.1 m, Downward Vision System enabled) Horizontal: ±4.92 feet (1.5 m) or ±0.98 feet (0.3 m, Downward Vision System enabled)		
Max Angular Velocity	Pitch: 300°/s, Yaw: 150°/s		
Max Pitch Angle	35° (In P-mode and Forward Vision System enabled: 25°)		
Max Ascent Speed	16.4 ft/s (5 m/s)		
Max Descent Speed (Vertical)	9.8 ft/s (3 m/s)		
Max Speed	P-mode: 61 kph(17 m/s); S-mode/A-mode: 83 kph (23 m/s)		
Max Service Ceiling Above Sea Level	3000 m		
Max Wind Resistance	32.8 ft/s (10 m/s)		
Max Flight Time (with standard batteries)	27 min (No payload), 13 min (Takeoff weight: 6.14 kg)		
Max Flight Time (with optional batteries)	38 (No payload), 24 min (Takeoff weight: 6.14 kg)		
Motor Model	DJI 3515		
Propeller Model	1760S		
Supported DJI Gimbals	Zenmuse X4S/X5S/XT/Z30		
Supported Gimbal Mounting	Single Downward Gimbal		
Waterproof Level	IP43		
GNSS	GPS+GLONASS		
Operating Temperature	-4° to 113° F (-20° to 45° C)		
Gimbal			
Angular Vibration Range	±0.01°		
Controllable Range	Pitch: -130° to +40°; Roll: ±20°; Pan: ±320°		
Max Controllable Speed	Pitch: 180°/s; Roll:180°/s; Pan:270°/s		
Interface Type	DGC2.0		
Mechanical Range	Pitch: -140° to +50°; Roll: -50° to +90°; Pan: ±330°		

Remote Controller	
Model	GL6D10A
Operating Frequency	2.400-2.483 GHz; 5.725-5.825 GHz
Max Transmitting Distance	2.4 GHz: 4.3 miles (7 km, FCC); 2.2 miles (3.5 km, CE); 2.5 miles (4 km, SRRC) 5.8 GHz: 4.3 miles (7 km, FCC); 1.2 miles (2 km, CE); 3.1 miles (5 km, SRRC)
EIRP	2.4 GHz: 26 dBm (FCC); 17 dBm (CE); 20 dBm (SRRC) 5.8 GHz: 28 dBm (FCC); 14 dBm (CE); 20 dBm (SRRC)
Video Output Ports	USB, HDMI
Power Supply	Built-in battery
Charging	DJI charger
Dual User Capability	Host-and-Slave connection
Mobile Device Holder	Tablet or Smart Phone
Max Mobile Device Width	170 mm
Output Power	9W (Without supplying power to smart device)
Operating Temperature	-4° to 104° F (-20° to 40° C)
Storage Temperature	Less than 3 months: -4° to 113° F (-20° to 45° C) More than 3 months: 72° to 82° F (22° to 28° C)
Charging Temperature	32° to 104° F (0° to 40° C)
Battery	6000 mAh 2S LiPo
USB Supply Power	iOS: 1 A = 5.2 V (Max); Android: 1.5 A = 5.2 V (Max)
Downward Vision System	
Velocity Range	<32.8 ft/s (10 m/s) at height of 6.56 feet (2 m)
Altitude Range	<32.8 feet (10 m)
Operating Range	<32.8 feet (10 m)
Operating Environment	Surfaces with clear patterns and adequate lighting (> 15 lux)
Ultrasonic Sensor Operating Range	0.33-16.4 feet (10-500 cm)
Ultrasonic Sensor Operating Environment	Non-absorbing material, rigid surface (thick indoor carpeting will reduce performance)
Forward Vision System	
Obstacle Sensing Range	2.3-98.4 feet (0.7-30 m)
FOV	Horizontal: 60°; Vertical: 54°
Operating Environment	Surfaces with clear patterns and adequate lighting (> 15 lux)
Upward Infrared Sensing System	
Obstacle Sensing Range	0-16.4 feet (0-5 m)
FOV	±5°
Operating Environment	Large, diffuse and reflective obstacles (reflectivity >10%)

Charger		
Model	IN2C180	
Voltage	26.1 V	
Rated Power	180 W	
Battery (Standard)		
Name	Intelligent Flight Battery	
Model	TB50-4280mAh-22.8V	
Capacity	4280 mAh	
Voltage	22.8 V	
Battery Type	6S LiPo	
Energy	97.58 Wh	
Net Weight	515 g	
Operating Temperature	-4° to 104° F (-20° to 40° C)	
Storage Temperature	Less than 3 months: -4° to 113° F (-20° to 45° C) More than 3 months: 72° to 82° F (22° to 28° C)	
Charging Temperature	41° to 104° F (5° to 40° C)	
Max Charging Power	180 W	
Charging Hub (Model: IN2CH)		
Input Voltage	26.1 V	
Input Current	6.9 A	
Battery (Standard)		
Name	Intelligent Flight Battery	
Model	TB55-7660 mAh-22.8V	
Capacity	7660 mAh	
Voltage	22.8 V	
Battery Type	6S LiPo	
Energy	176.93 Wh	
Net Weight	885 g	
Operating Temperature	-4° to 104° F (-20° to 40° C)	
Storage Temperature	Less than 3 months: -4° to 113° F (-20° to 45° C) More than 3 months: 72° to 82° F (22° to 28° C)	
Charging Temperature	41° to 104° F (5° to 40° C)	
Max Charging Power	180 W	

	•	
Normal		
(R) (Y) (G) (B) (P) ·····	Red, yellow, green, blue, and purple flashes	Power on and self-check
· (\$\tilde{\ti}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}	Green and Yellow Flash Alternatively	Aircraft warming up
-`````	Green Flashes Slowly	Safe to Fly (P-mode with GPS and Vision System)
ĞX2⋯⋯	Green Flashes Twice	Safe to Fly (P-mode with Vision System but without GPS)
- <u>`</u> \'\'	Yellow Flashes Slowly	Safe to Fly (A-mode but No GPS and Vision System)
Warning		
· \( \times \)	Fast Yellow Flashing	Remote Controller Signal Lost
- <u>`</u> ®	Slow Red Flashing	Low Battery Warning
- <u>R</u>	Fast Red Flashing	Critical Low Battery Warning
· · · · · · · ·	Red Flashing Alternatively	IMU Error
- ®-	Solid Red	Critical Error
· · · · · · · · · · · · · · · · · · ·	Red and Yellow Flash Alternatively	Compass Calibration Required

# Upgrading the Firmware

Aircraft Status Indicator Description

Use DJI Assistant 2 or the DJI GO 4 app to upgrade the aircraft and remote controller.

# Upgrading the Aircraft Firmware

For the Zenmuse X5S and X4S, M200 aircraft and gimbal firmware will be updated simultaneously via DJI Assistant 2 or the DJI GO 4 app.

For the Zenmuse Z30 and XT, only M200 aircraft firmware can be updated via DJI Assistant 2 or the DJI GO 4 app. Gimbal firmware must be updated via a Micro SD card.

#### Method 1: Using DJI Assistant 2

- 1. Power on the Intelligent Flight Battery and toggle the USB Mode Switch left.
- 2. Connect the Matrice 200 and the PC via the USB cable (with Double A ports).
- 3. Launch DJI Assistant 2 and login with a DJI account.
- 4. Click M200SERIES and the firmware update button.
- 5. Select the firmware version required.
- 6. DJI Assistant 2 will download and upgrade the firmware automatically.
- 7. Restart the aircraft after the firmware upgrade is complete.

#### Method 2: Using the DJI GO 4 App

- 1. Power on the Intelligent Flight Battery and toggle the USB Mode Switch right.
- 2. Connect the aircraft and your mobile device via an appropriate USB cable.
- Follow the on-screen instructions in the DJI GO 4 app to upgrade. Ensure to connect to the Internet when downloading the firmware.
- 4. Restart the aircraft after the firmware update is complete.



- The firmware update will take around 15 minutes. It is normal that the gimbal will go limp, the aircraft status indicator blinks abnormally when the aircraft reboots. Wait patiently until the update is complete.
- During an update, the aircraft will sound a quick single beep continuously. The warning sound will then alternate between a longer beep and a quick double beep once the update is complete. Restart the aircraft after the firmware update is complete.
- If the warning sound turns into a long beep, retry the update.
- The battery level should be above 30% for the firmware update process.
- When using DJI GO 4 to update, you may disconnect the aircraft and the mobile device once the update is more than 30% completed. No Internet connection is required.

# Upgrading the Remote Controller Firmware

## Method 1: Using the DJI GO 4 App

Power on the remote controller and connect it with the DJI GO 4 app. A prompt will appear if a new firmware upgrade is available. To start upgrading, connect a mobile device to the Internet and follow the on-screen instructions.



- Ensure the battery level is adequate for the remote controller.
- Do not disconnect the aircraft from the computer during a firmware upgrade.

# After-Sales Information

Visit the following pages to learn more about our After-sales Service Policy and warranty information:

- 1. After-sales Policy: http://www.dji.com/service
- 2. Refund Policy: http://www.dji.com/service/refund-return
- 3. Paid Repair Service: http://www.dji.com/service/repair-service
- 4. Warranty Service: http://www.dji.com/service/warranty-service

This content is subject to change.

# Download the latest version from http://www.dji.com/matrice-200-series

