PHANTOM SLIDE LEVER INSTRUCTION VI.00 PHANTOM辅助摇杆说明V1.00

The Slide Lever can be used for gimbal tilt control. 辅助採杆可用于控制云台俯仰运动。

- 1. Remove the screws on the back of the Transmitter to open the rear cover. Fig.1 shows the Mount position. 制下谣控器背面的螺丝、打开后盖。安装位置如图1。
- 2. (Fig.2) Peer off the sticker on double-sided tape. (Fig.3) Mount the Slide Lever with the screw (MZ.0x4.5). Thread locker is not recommended. Make sure the Slide Lever can slide smoothly, 如图2撕掉双面胶上的贴纸,并按照图3安装, 适当用力拧紧 MZ.0x4.5螺丝, 不建议使用螺丝胶。请确保辅助据杆可轻松 摆动。
- Make sure the Slide Lever is in the correct position (Fig.4) and the cross-head is properly fitted into the cross-slot (Fig.5) and then reinstall the rear cover and fix the screws to finish the installation. You can confirm the correct installation in Assistant software: Basic-SRC-SSTicks Monitor.

确保摇杆拨到正确位置(如图4)同时摇杆轴端正确插入电位器十字槽(如图5),然后重新安装遥控器后壳并拧紧螺丝,安装完毕。您可以在调参软件:基础~遥控器~遥控杆 监视面面验证安装是否OK.



Fig.1 Mount position 图1 安装位置



Fig.2 Use double-sided tape 图2 使用双面胶



Fig.3 Mount the Slide Lever

图3安装辅助摇杆



Fig.4 Correct Installation 图4 正确安装示意图



Fig.5 Assembly detail 图5 安装细节示意图